1994 *FPJ* SUBJECT AND AUTHOR INDEX

All of the articles in the 1994 *Forest Products Journal*, volume 44, are listed both by subject and by author. The Subject Index is organized according to the Forest Products Society Division and Technical Interest Group structure. The Author Index lists senior author entries that give complete information for the article, and coauthor entries that refer back to the senior author. Reprints of most articles are available at $5 each. Bulk rates are also available. Please give reprint numbers when ordering. When printer-quality reprints are no longer available, photocopies can be ordered at 50 cents per page. All orders are subject to a $5 minimum charge plus 15 percent shipping and handling, 20 percent in other countries.

COMPOSITE & MANUFACTURED PRODUCTS

Furniture & Hardwood Veneer/Plywood

Color Analysis of White Oak, Edge-Glued Furniture Panel Stock, J.E. Phelps, D.D. Stokke, and A.D. Pugel, 2:35-38 (No. 8056).

Furniture Markets as Promotional Tools: Integrating Objectives for Furniture Manufacturers, J.H. Michael and P.M. Smith, 11/12:51-54 (No. 8138).

Influence of Product and Supplier Attributes on Hardwood Lumber Purchase Decisions in the Furniture Industry, C.L. Forbes, S.A. Sinclair, R.J. Bush, and P.A. Araman, 2:51-56 (No. 8048).

The Use of Performance Tests in Evaluating Joint and Fastener Strength in Case Furniture, C.L. Ho and C.A. Eckelman, 9:47-53 (No. 7922).

Yield Comparison of Furniture Parts for Three Gang-Ripping Systems, P.H. Steele and S. Lee, 3:9-16 (No. 8009).

Gluing

Adhesive Bonding of Pultruded Fiber Reinforced Plastic to Wood, D.J. Gardner, J.F. Davalos, and U.M. Munipalle, 5:62-66 (No. 8104).

Carbohydrate-Based Extender for Wood-Particulate Composites, S.E. Johnson and F.A. Kamke, 3:46-48 (No. 7879).

Comparison of Strandboards Made With Phenol-Formaldehyde Resin and Resins Modified With TVA Acid-Hydrolysis Lignin, T. Sellers, Jr., M.G. Kim, G.D. Miller, R.A. Haupt, and R.C. Strickland, 4:63-68 (No. 8022).

Effect of Glueline Voids on the Tensile Strength of Finger-Jointed Wood, P.J. Pellicane, R.M. Gutkowski, and C. Jauslin, 6:61-65 (No. 8129).

Effect of Polyisocyanate Level on Physical Properties of Wood Fiber Composite Materials, B.C.H. Sun, R.N. Hawke, and M.R. Gale, 4:53-58 (No. 7979).

Effect of Polyisocyanate Level on Strength Properties of Wood Fiber Composite Materials, B.C.H. Sun, R.N. Hawke, and M.R. Gale, 3:34-40, (No. 7978).

Effect of Two Wood Surfacing Methods on the Gluing Properties of Sugar Maple and White Spruce, R.E. Hernández, 7/8:63-66 (No. 8088).

Evaluation of Phenol-Formaldehyde OSB Resins Modified With Lignin Residues From Acid-Hydrolyzed Waste Newsprint, Y. Oh, T. Sellers, Jr., M.G. Kim, and R.C. Strickland, 2:25-29 (No. 8042).

Phenolic Adhesive Bonds to Aspen Veneers Treated With Amino-Resin Fire Retardants, C.B. Vick, 1:33-40 (No. 7977).

Phenolic Resin-Wood Interaction, R.A. Haupt and T. Sellers, Jr., 2:69-73 (No. 8030).

Total Phenolic Compounds and Free Phenol in Softwood Structural Plywood, G.T. Tiedeman, R.L. Isaacson, and T. Sellers, Jr., 3:73-75 (No. 8043).

Hardboard & Insulation Board

Using Competitive Analysis Models to Set Strategy in the Northwest Hardboard Industry, W.P. Munk and B. Shane, 7/8:11-18 (No. 7995).

Particleboard &Molded Products

Recycled Fiber Quality From a Laboratory-Scale Blade Separator/Blender, B-H. Liang, S.M. Shaler, L. Mott, and L. Groom, 7/8:47-50 (No. 8113).

The Use of Performance Tests in Evaluating Joint and Fastener Strength in Case Furniture, C.L. Ho and C.A. Eckelman, 9:47-53 (No. 7922).

Variation in Selected Properties of Industrial Grade Particleboard, D.L. Cassens, J.P. Bradtmueller, and F. Picado, 10:50-56 (No. 8144).

Structural Panels

Basic Mechanical Properties of Flakeboards from Ring-Cut Flakes of Eastern Hardwoods, C.G. Carll, 9:26-32 (No. 8105).

Carbohydrate-Based Extender for Wood-Particulate Composites, S.E. Johnson and F.A. Kamke, 3:46-48 (No. 7879).

Comparison of Strandboards Made With Phenol-Formaldehyde Resin and Resins Modified With TVA Acid-Hydrolysis Lignin, T. Sellers, Jr., M.G. Kim, G.D. Miller, R.A. Haupt, and R.C. Strickland, 4:63-68 (No. 8022).

Compressive Strength of Hardwood-Cement Composites, P.R. Blankenhorn, P. Labosky, Jr., M. DiCola, and L.R. Stover, 4:59-62 (No. 7962).

Creep Behavior of Sweetgum OSB: Effect of Load Level and Relative Humidity, J.H. Pu, R.C. Tang, and C.Y. Hse, 11/12:45-50 (No. 8064).

Development of the Five-Point Bending Test to Determine Shear Moduli of Wood Composites, J.P. Bradtmueller, M.O. Hunt, K.J. Fridley, and G.P. McCabe, 5:17-26 (No. 8090).

The Durability of Phenolic-Bonded Particleboards Made of Decay-Resistant Black Locust and Nondurable Aspen, D.P. Kamdem and S.T. Sean, 2:65-68 (No. 8016).

Effect of Polyisocyanate Level on Physical Properties of Wood Fiber Composite Materials, B.C.H. Sun, R.N. Hawke, and M.R. Gale, 4:53-58 (No. 7979).

Effect of Polyisocyanate Level on Strength Properties of Wood Fiber Composite Materials, B.C.H. Sun, R.N. Hawke, and M.R. Gale, 3:34-40, (No. 7978).

Outdoor Aging of Wood-Based Panels and Correlation With Laboratory Aging, B.H. River, 11/12:55-65 (No.8106).

Phenolic Resin-Wood Interaction, R.A. Haupt and T. Sellers, Jr., 2:69-73 (No. 8030).

Steam-Assisted Hot-Pressing of Construction Plywood, R.W. Jokerst and R.L. Geimer, 11/12:34-36 (No. 7838).

Use of Disodium Octaborate Tetrahydrate to Protect Aspen Waferboard From Termites, T.G. Myles, 9:33-36 (No. 8143).

1994 *FPJ* SUBJECT AND AUTHOR INDEX

All of the articles in the 1994 *Forest Products Journal*, volume 44, are listed both by subject and by author. The Subject Index is organized according to the Forest Products Society Division and Technical Interest Group structure. The Author Index lists senior author entries that give complete information for the article, and coauthor entries that refer back to the senior author. Reprints of most articles are available at $5 each. Bulk rates are also available. Please give reprint numbers when ordering. When printer-quality reprints are no longer available, photocopies can be ordered at 50 cents per page. All orders are subject to a $5 minimum charge plus 15 percent shipping and handling, 20 percent in other countries.

COMPOSITE & MANUFACTURED PRODUCTS

Furniture & Hardwood Veneer/Plywood

Color Analysis of White Oak, Edge-Glued Furniture Panel Stock, J.E. Phelps, D.D. Stokke, and A.D. Pugel, 2:35-38 (No. 8056).

Furniture Markets as Promotional Tools: Integrating Objectives for Furniture Manufacturers, J.H. Michael and P.M. Smith, 11/12:51-54 (No. 8138).

Influence of Product and Supplier Attributes on Hardwood Lumber Purchase Decisions in the Furniture Industry, C.L. Forbes, S.A. Sinclair, R.J. Bush, and P.A. Araman, 2:51-56 (No. 8048).

The Use of Performance Tests in Evaluating Joint and Fastener Strength in Case Furniture, C.L. Ho and C.A. Eckelman, 9:47-53 (No. 7922).

Yield Comparison of Furniture Parts for Three Gang-Ripping Systems, P.H. Steele and S. Lee, 3:9-16 (No. 8009).

Gluing

Adhesive Bonding of Pultruded Fiber Reinforced Plastic to Wood, D.J. Gardner, J.F. Davalos, and U.M. Munipalle, 5:62-66 (No. 8104).

Carbohydrate-Based Extender for Wood-Particulate Composites, S.E. Johnson and F.A. Kamke, 3:46-48 (No. 7879).

Comparison of Strandboards Made With Phenol-Formaldehyde Resin and Resins Modified With TVA Acid-Hydrolysis Lignin, T. Sellers, Jr., M.G. Kim, G.D. Miller, R.A. Haupt, and R.C. Strickland, 4:63-68 (No. 8022).

Effect of Glueline Voids on the Tensile Strength of Finger-Jointed Wood, P.J. Pellicane, R.M. Gutkowski, and C. Jauslin, 6:61-65 (No. 8129).

Effect of Polyisocyanate Level on Physical Properties of Wood Fiber Composite Materials, B.C.H. Sun, R.N. Hawke, and M.R. Gale, 4:53-58 (No. 7979).

Effect of Polyisocyanate Level on Strength Properties of Wood Fiber Composite Materials, B.C.H. Sun, R.N. Hawke, and M.R. Gale, 3:34-40, (No. 7978).

Effect of Two Wood Surfacing Methods on the Gluing Properties of Sugar Maple and White Spruce, R.E. Hernández, 7/8:63-66 (No. 8088).

Evaluation of Phenol-Formaldehyde OSB Resins Modified With Lignin Residues From Acid-Hydrolyzed Waste Newsprint, Y. Oh, T. Sellers, Jr., M.G. Kim, and R.C. Strickland, 2:25-29 (No. 8042).

Phenolic Adhesive Bonds to Aspen Veneers Treated With Amino-Resin Fire Retardants, C.B. Vick, 1:33-40 (No. 7977).

Phenolic Resin-Wood Interaction, R.A. Haupt and T. Sellers, Jr., 2:69-73 (No. 8030).

Total Phenolic Compounds and Free Phenol in Softwood Structural Plywood, G.T. Tiedeman, R.L. Isaacson, and T. Sellers, Jr., 3:73-75 (No. 8043).

Hardboard & Insulation Board

Using Competitive Analysis Models to Set Strategy in the Northwest Hardboard Industry, W.P. Munk and B. Shane, 7/8:11-18 (No. 7995).

Particleboard &Molded Products

Recycled Fiber Quality From a Laboratory-Scale Blade Separator/Blender, B-H. Liang, S.M. Shaler, L. Mott, and L. Groom, 7/8:47-50 (No. 8113).

The Use of Performance Tests in Evaluating Joint and Fastener Strength in Case Furniture, C.L. Ho and C.A. Eckelman, 9:47-53 (No. 7922).

Variation in Selected Properties of Industrial Grade Particleboard, D.L. Cassens, J.P. Bradtmueller, and F. Picado, 10:50-56 (No. 8144).

Structural Panels

Basic Mechanical Properties of Flakeboards from Ring-Cut Flakes of Eastern Hardwoods, C.G. Carll, 9:26-32 (No. 8105).

Carbohydrate-Based Extender for Wood-Particulate Composites, S.E. Johnson and F.A. Kamke, 3:46-48 (No. 7879).

Comparison of Strandboards Made With Phenol-Formaldehyde Resin and Resins Modified With TVA Acid-Hydrolysis Lignin, T. Sellers, Jr., M.G. Kim, G.D. Miller, R.A. Haupt, and R.C. Strickland, 4:63-68 (No. 8022).

Compressive Strength of Hardwood-Cement Composites, P.R. Blankenhorn, P. Labosky, Jr., M. DiCola, and L.R. Stover, 4:59-62 (No. 7962).

Creep Behavior of Sweetgum OSB: Effect of Load Level and Relative Humidity, J.H. Pu, R.C. Tang, and C.Y. Hse, 11/12:45-50 (No. 8064).

Development of the Five-Point Bending Test to Determine Shear Moduli of Wood Composites, J.P. Bradtmueller, M.O. Hunt, K.J. Fridley, and G.P. McCabe, 5:17-26 (No. 8090).

The Durability of Phenolic-Bonded Particleboards Made of Decay-Resistant Black Locust and Nondurable Aspen, D.P. Kamdem and S.T. Sean, 2:65-68 (No. 8016).

Effect of Polyisocyanate Level on Physical Properties of Wood Fiber Composite Materials, B.C.H. Sun, R.N. Hawke, and M.R. Gale, 4:53-58 (No. 7979).

Effect of Polyisocyanate Level on Strength Properties of Wood Fiber Composite Materials, B.C.H. Sun, R.N. Hawke, and M.R. Gale, 3:34-40, (No. 7978).

Outdoor Aging of Wood-Based Panels and Correlation With Laboratory Aging, B.H. River, 11/12:55-65 (No.8106).

Phenolic Resin-Wood Interaction, R.A. Haupt and T. Sellers, Jr., 2:69-73 (No. 8030).

Steam-Assisted Hot-Pressing of Construction Plywood, R.W. Jokerst and R.L. Geimer, 11/12:34-36 (No. 7838).

Use of Disodium Octaborate Tetrahydrate to Protect Aspen Waferboard From Termites, T.G. Myles, 9:33-36 (No. 8143).

FUNDAMENTAL DISCIPLINES

Biology

Discolorations of Hem-fir Wood: A Review of the Mechanisms, B. Kreber and A. Byrne, 5:35-42 (No. 8093).

Distribution of Biocides in Douglas-fir Poles 42 Months After Application of Groundline Preservative Systems, J.J. Morrell, P.G. Forsyth, and M.A. Newbill, 6:24-27 (No. 8120).

The Effect of Frost Cracks in Sugar Pine Trees on Lumber Grade, E.C. Lowell and T.D. Fahey, 10:57-60 (No. 8033).

Evaluating Pruned Sawlog Quality and Assessing Sawmill Recoveries in New Zealand, J.C. Park, 4:43-52 (No. 8044).

Evaluation of a Radio-Frequency/Vacuum Dryer for Eradicating the Pinewood Nematode in Green Sawn Wood, L.D. Dwinell, S. Avramidis, and J.E. Clark, 4:19-24 (No. 8050).

Fungal Decay Resistance of Aspen Blocks Treated With Heartwood Extracts, D.P. Kamdem, 1:30-32 (No. 8031).

Longitudinal Shrinkage in Fast-Grown Loblolly Pine Plantation Wood, L. Ying, D.E. Kretschmann, and B.A. Bendtsen, 1:58-62 (No. 8006).

A Method of Testing the Full Cross Section of Wood in Tension Perpendicular to the Grain, T.D. Faust, M. Fuller, and J.T. Rice, 3:23-26 (No. 7976).

Natural Resistance of Alaska-cedar, Redwood, and Teak to Formosan Subterranean Termites, J.K. Grace and R.T. Yamamoto, 3:41-45 (No. 8062).

Prevention of Enzyme Stain of Hardwoods by Log Fumigation, E.L. Schmidt and T.L. Amburgey, 5:32-34 (No. 8068).

Stiffness of Wood in Fast-Grown Plantation Softwoods: The Influence of Microfibril Angle, I.D. Cave and J.C.F. Walker, 5:43-48 (No. 8087).

Chemistry

Evaluation of Phenol-Formaldehyde OSB Resins Modified With Lignin Residues From Acid-Hydrolyzed Waste Newsprint, Y. Oh, T. Sellers, Jr., M.G. Kim, and R.C. Strickland, 2:25-29 (No. 8042).

Why Does Douglas-fir Heartwood Turn Black When Treated With Ammoniacal Copper Preservatives? J.N.R. Ruddick and C. Xie, 2:57-61 (No. 8054).

Physics

The Effects of Directed Diffusion on the Mechano-Sorptive Behavior of Small Redwood Beams, W. Lu and R.W. Erickson, 1:8-14 (No. 8015).

Effect of Hot-Water Soaking or Freezing Pretreatments on the Drying Rates of Two Eucalypts, B.R. Glossop, 10:29-32 (No. 7959).

Effects of Long-Term Elevated Temperature on CCA-Treated Southern Pine Lumber, J.E. Winandy, 6:49-56 (No. 8114).

Modeling Intratree Wood Shrinkage in European Oak by Measuring Wood Density, S.Y. Zhang, G. Nepveu, and F. Mothe, 10:42-46 (No. 8086).

Outdoor Aging of Wood-Based Panels and Correlation With Laboratory Aging, B.H. River, 11/12:55-65 (No.8106).

Resistance Moisture Meter Correction Factor for Pacific Yew, W.T. Simpson and S.P. Loehnertz, 1:63-64 (No. 8020).

Specific Gravity as a Predictor of Species Correction Factors for a Capacitance-Type Moisture Meter, M.R. Milota, 3:63-68 (No. 8066).

A Technique to Electrically Measure the Moisture Content of Wood Above Fiber Saturation, Z. Chen, E.M. Wengert, and F.M. Lamb, 9:57-62 (No. 8053).

MANAGEMENT

Application of Technology

Information Processing Systems for General Access of Unpublished Wood Products Research Data, T. Sellers, Jr., 6:33-39 (No. 8041).

Marketing

Benefits From Market Timing Controls in Sawmill Production Management, T.C. Maness, 5:27-31 (No. 8091).

Customer-Oriented Marketing Method for Hardwood Lumber Companies, J.O. Idassi, T.M. Young, P.M. Winistorfer, D.M. Ostermeier, and R.B. Woodruff, 7/8:67-73 (No. 8003).

Distribution and Marketing of Southern Yellow Pine Shakes: Potential for Expansion, C.T. Horton, J.H. Syme, C.R. Duke, and T.J. Straka, 11/12:21-26 (No. 8156).

Export Assistance in the Hardwood Industry: An Examination of Awareness, Use, and Perceived Benefit, P.A. Ifju and R.J. Bush, 6:27-33 (No. 8071).

Furniture Markets as Promotional Tools: Integrating Objectives for Furniture Manufacturers, J.H. Michael and P.M. Smith, 11/12:51-54 (No. 8138).

Influence of Product and Supplier Attributes on Hardwood Lumber Purchase Decisions in the Furniture Industry, C.L. Forbes, S.A. Sinclair, R.J. Bush, and P.A. Araman, 2:51-56 (No. 8048).

International Trade in Forest Products: An Overview, G.D. Puttock, M. Sabourin, and K.D. Meilke, 3:49-56 (No. 8067).

Marketing Practices in the Timber Bridge Industry, R.L. Smith and R.J. Bush, 11/12:27-33 (No. 8163).

Market-Oriented Strategy for Forest-Based Rural Economic Development, J.H. Syme and C.R. Duke, 5:10-16 (No. 8028).

The Retail Homecenter Perspective on Point-of-Sale Scanning of UPC Barcoded Wood Products, R.P. Vlosky and P.M. Smith, 7/8:27-33 (No. 8107).

The U.S. Hardwood Log Export Situation: What is the Problem? W.G. Luppold, 9:63-67 (No. 8155).

Using Competitive Analysis Models to Set Strategy in the Northwest Hardboard Industry, W.P. Munk and B. Shane, 7/8:11-18 (No. 7995).

Wood Products Used in New Single-Family House Construction: 1950 to 1992, D.B. McKeever and R.B. Phelps, 11/12:66-74 (No. 8169).

Quality Control

An Assessment of Quality Control in British Columbia Sawmills: Production, Employment, Trends, and Priorities, T.C. Maness, D.H. Cohen, and R. Smith, 3:27-33 (No. 8001).

PROCESSES

Drying & Storage

Changes in the Kiln-Drying Practices of the Forest Products Industry in West Virginia: 1982 to 1992, J.P. Armstrong and T.L. Pahl, 9:54-56 (No. 8134).

Drying Thick Western Hemlock in a Laboratory Radio-Frequency/Vacuum Dryer With Constant and Variable Electrode Voltage, F. Liu, S. Avramidis, and R.L. Zwick, 6:71-76 (No. 8099).

Effect of Hot-Water Soaking or Freezing Pretreatments on the Drying Rates of Two Eucalypts, B.R. Glossop, 10:29-32 (No. 7959).

Evaluation of a Radio-Frequency/Vacuum Dryer for Eradicating the Pinewood Nematode in Green Sawn Wood, L.D. Dwinell, S. Avramidis, and J.E. Clark, 4:19-24 (No. 8050).

Radio-Frequency/Vacuum Drying of Softwoods: Drying of Thick Western Redcedar With Constant Electrode Voltage, S. Avramidis, F. Liu, and B.J. Neilson, 1:41-47 (No. 8004).

Resistance Moisture Meter Correction Factor for Pacific Yew, W.T. Simpson and S.P.

Loehnertz, 1:63-64 (No. 8020).

Specific Gravity as a Predictor of Species Correction Factors for a Capacitance-Type Moisture Meter, M.R. Milota, 3:63-68 (No. 8066).

Statistical Process Control of Hardwood Lumber Target Sizes: Is It Time? D.L. Cassens, J.R. Bankston, and J.S. Friday, 1:48-50 (No. 7971).

A Survey of Firms Kiln-Drying Lumber in the United States: Volume, Species, Kiln Capacity, Equipment, and Procedures, R.W. Rice, J.L. Howe, R.S. Boone, and J.L. Tschernitz, 7/8:55-62 (No. 8149).

A Technique to Electrically Measure the Moisture Content of Wood Above Fiber Saturation, Z. Chen, E.M. Wengert, and F.M. Lamb, 9:57-62 (No. 8053).

Energy Generation & Conservation

Conventional Fuel Displacement by Residential Wood Use, K. Warsco, 1:68-74 (No. 7900).

Finishing & Overlaying

Comparative Weathering Tests of North American and European Exterior Wood Finishes, F.W. Kropf, J. Sell, and W.C. Feist, 10:33-41 (No. 8132).

Weathering Performance of Finished Aspen Siding, W.C. Feist, 6:15-24 (No. 8122).

Milling & Machining

An Assessment of Quality Control in British Columbia Sawmills: Production, Employment, Trends, and Priorities, T.C. Maness, D.H. Cohen, and R. Smith, 3:27-33 (No. 8001).

Crosscut Optimization of Boards Given Complete Defect Information, E. Åstrand and M. Rönnqvist, 2:15-24 (No. 8008).

Dimension Yields From Factory Grade 2 and 3 Red Oak Logs, W. Lin, D.E. Kline, and P.A. Araman, 9:19-25 (No. 8109).

Evaluating Pruned Sawlog Quality and Assessing Sawmill Recoveries in New Zealand, J.C. Park, 4:43-52 (No. 8044).

Increased Lumber Value From Optimum Orientation of Internal Defects With Respect to Sawing Pattern in Hardwood Sawlogs, P.H. Steele, T.E.G. Harless, F.G. Wagner, L. Kumar, and F.W. Taylor, 3:69-72 (No. 7871).

Prediction Equations for Determining Board Foot Recovery From Bolter Saw Bolts, D.W. Patterson and J.P. Armstrong, 4:40-42 (No. 8084).

TRSys: A Hardwood Lumber Grading Training and Remanufacturing System, R. Klinkhachorn, R. Kothari, R. Annavajjhala, and C.W. McMillin, 9:68-72 (No. 7916).

Yield Comparisons of Furniture Parts for Three Gang-Ripping Systems, P.H. Steele and S. Lee, 3:9-16 (No. 8009).

Process Control

Steam-Assisted Hot-Pressing of Construction Plywood, R.W. Jokerst and R.L. Geimer, 11/12:34-36 (No. 7838).

Timber Production & Harvesting

Effect of Initial Spacing and Thinning on Lumber Grade, Yield, and Strength of Loblolly Pine, A. Clark III, J.R. Saucier, V.C. Baldwin, and D.R. Bower, 11/12:14-20 (No. 8159).

Evaluating Pruned Sawlog Quality and Assessing Sawmill Recoveries in New Zealand, J.C. Park, 4:43-52 (No. 8044).

Evaluation of Logger Continuing Education Needs in Minnesota, M.F. Smidt and C.R. Blinn, 3:57-62 (No. 8034).

An Expert System for Timber Harvesting Decision Making on Industrial Forest Lands, P.E. Linehan and T.J. Corcoran, 6:65-71 (No. 8092).

Inventory of Land Management Inputs for Producing Absorbent Fibers for Diapers: A Comparison of Cotton and Softwood Land Management, B.N. Johnson, 6:39-46 (No. 8103).

Log Separation Economics on In-Woods Chipping Operations, W.D. Greene and J.S. Carruth, 10:68-72 (No. 8152).

Managerial and Operational Characteristics of "Safety Successful" Logging Contractors, T.W. Reisinger, R.G. Sluss, and R.M. Shaffer, 4:72-77 (No. 8065).

Optimal Yarding Road Width Model for Skyline Yarding, J.F. McNeel and G.G. Young, 2:45-50 (No. 7992).

Regulating for Sustained Yield: A Review of Some Fundamental Relationships, C. Schallau, J. Heissenbuttel, and R. Pierson, 7/8:23-26 (No. 8100).

Residual Tree Damage Estimates From Partial Cutting Simulation, W.C. Bragg, W.D. Ostrofsky, and B.F. Hoffman, Jr., 7/8:19-22 (No. 8077).

SOLID WOOD PRODUCTS

Hardwood Lumber

Compression Strength Properties for Two Hardwood Glulam Materials, J.J. Janowiak, K.R. Kessler, H.B. Manbeck, P.R. Blankenhorn, and P. Labosky, 2:62-64 (No. 8045).

Crosscut Optimization of Boards Given Complete Defect Information, E. Åstrand and M. Rönnqvist, 2:15-24 (No. 8008).

Customer-Oriented Marketing Method for Hardwood Lumber Companies, J.O. Idassi, T.M. Young, P.M. Winistorfer, D.M. Ostermeier, and R.B. Woodruff, 7/8:67-73 (No. 8003).

Dimension Yields From Factory Grade 2 and 3 Red Oak Logs, W. Lin, D.E. Kline, and P.A. Araman, 9:19-25 (No. 8109).

Effect of Hot-Water Soaking or Freezing Pretreatments on the Drying Rates of Two Eucalypts, B.R. Glossop, 10:29-32 (No. 7959).

Export Assistance in the Hardwood Industry: An Examination of Awareness, Use, and Perceived Benefit, P.A. Ifju and R.J. Bush, 6:27-33 (No. 8071).

Factors Affecting Regional Changes in Hardwood Lumber Production, W.G. Luppold and G.P. Dempsey, 6:8-15 (No. 7974).

Increased Lumber Value From Optimum Orientation of Internal Defects With Respect to Sawing Pattern in Hardwood Sawlogs, P.H. Steele, T.E.G. Harless, F.G. Wagner, L. Kumar, and F.W. Taylor, 3:69-72 (No. 7871).

Influence of Product and Supplier Attributes on Hardwood Lumber Purchase Decisions in the Furniture Industry, C.L. Forbes, S.A. Sinclair, R.J. Bush, and P.A. Araman, 2:51-56 (No. 8048).

Methyl Bromide Fumigation to Control Non-Microbial Discolorations in Western Hemlock and Red Alder, B. Kreber, E.L. Schmidt, and T. Byrne, 10:63-67 (No. 8150).

Modeling Intratree Wood Shrinkage in European Oak by Measuring Wood Density, S.Y. Zhang, G. Nepveu, and F. Mothe, 10:42-46 (No. 8086).

Performance of Oak Strip Flooring Systems Under Changing Environmental Conditions, E.M. Lang, J.R. Loferski, T.E. McLain, and C.M. Moore, 5:54-61 (No. 7993).

Prediction Equations for Determining Board Foot Recovery From Bolter Saw Bolts, D.W. Patterson and J.P. Armstrong, 4:40-42 (No. 8084).

A Profile of the U.S. Pallet and Container Industry, J.D. Christoforo, R.J. Bush, and W.G. Luppold, 2:9-14 (No. 8047).

Rough Mill Policies Examined by a Multiple-Criteria Goal Program Called ROMGOP, W.C. Suter, Jr. and J.A. Calloway, 10:19-28 (No. 8069).

Statistical Process Control of Hardwood Lumber Target Sizes: Is It Time? D.L. Cassens, J.R. Bankston, and J.S. Friday, 1:48-50 (No. 7971).

The U.S. Hardwood Log Export Situation: What is the Problem? W.G. Luppold, 9:63-67 (No. 8155).

TRSys: A Hardwood Lumber Grading Training and Remanufacturing System, R. Klinkhachorn, R. Kothari, R. Annavajjhala, and C.W. McMillin, 9:68-72 (No. 7916).

Yield Comparisons of Furniture Parts for Three Gang-Ripping Systems, P.H. Steele and S. Lee, 3:9-16 (No. 8009).

Softwood Lumber

Benefits From Market Timing Controls in Sawmill Production Management, T.C. Maness, 5:27-31 (No. 8091).

Color Analysis of White Oak, Edge-Glued Furniture Panel Stock, J.E. Phelps, D.D. Stokke, and A.D. Pugel, 2:35-38 (No. 8056).

Comparison of Empty-Cell and Full-Cell Treatment of Red Pine and Lodgepole Pine Pole Sections With CCA-PEG, P.A. Cooper, Y.T. Ung, and C. Timusk, 4:13-18 (No. 8082).

A Comparison of Some Physical and Mechanical Properties of Full-Sib and Half-Sib Loblolly Pines, R.H. McAlister and H.R. Powers, 2:42-44 (No. 7987).

Dahurian Larch: Treatment With Inorganic Arsenical Perservatives, J.J. Morrell and P.F. Schneider, 10:61-62 (No. 8162).

Discolorations of Hem-fir Wood: A Review of the Mechanisms, B. Kreber and A. Byrne, 5:35-42 (No. 8093).

Distribution and Marketing of Southern Yellow Pine Shakes: Potential for Expansion, C.T. Horton, J.H. Syme, C.R. Duke, and T.J. Straka, 11/12:21-26 (No. 8156).

Drying Thick Western Hemlock in a Laboratory Radio-Frequency/Vacuum Dryer With Constant and Variable Electrode Voltage, F. Liu, S. Avramidis, and R.L. Zwick, 6:71-76 (No. 8099).

The Effect of Frost Cracks in Sugar Pine Trees on Lumber Grade, E.C. Lowell and T.D. Fahey, 10:57-60 (No. 8033).

Effect of Initial Spacing and Thinning on Lumber Grade, Yield, and Strength of Loblolly Pine, A. Clark III, J.R. Saucier, V.C. Baldwin, and D.R. Bower, 11/12:14-20 (No. 8159).

Effects of Long-Term Elevated Temperature on CCA-Treated Southern Pine Lumber, J.E. Winandy, 6:49-56 (No. 8114).

Efficacy of Pressure Treating Northeastern Red Spruce With CCA Using the Pulsation Process, K.A. Flynn and B.S. Goodell, 10:47-49 (No. 8154).

Localized Modulus-of-Elasticity Properties of E-Rated Spruce-Pine Laminating Lumber, R. Govindarajoo, R.F. Pellerin, and R.J. Ross, 4:25-32 (No. 8061).

Longitudinal Shrinkage in Fast-Grown Loblolly Pine Plantation Wood, L. Ying, D.E. Kretschmann, and B.A. Bendtsen, 1:58-62 (No. 8006).

Methyl Bromide Fumigation to Control Non-Microbial Discolorations in Western Hemlock and Red Alder, B. Kreber, E.L. Schmidt, and T. Byrne, 10:63-67 (No. 8150).

Radio-Frequency/Vacuum Drying of Softwoods: Drying of Thick Western Redcedar With Constant Electrode Voltage, S. Avramidis, F. Liu, and B.J. Neilson, 1:41-47 (No. 8004).

Shear and Compression Perpendicular to Grain Property Estimation for 2400f MSR Lumber, D.W. Green, D.E. Kretschmann, and J.A. Fantozzi, 11/12:75-81 (No. 8079).

Stiffness of Wood in Fast-Grown Plantation Softwoods: The Influence of Microfibril Angle, I.D. Cave and J.C.F. Walker, 5:43-48 (No. 8087).

Stress Wave Nondestructive Evaluation of Wetwood, R.J. Ross, J.C. Ward, and A. Ten-Wolde, 7/8:79-83 (No. 8136).

Treated Wood Products

Characteristics of Creosote-Treated LVL Materials, J.D. Kimmel, J.J. Janowiak, R.T. Baileys, and P. Merrick, 5:49-53 (No. 8108).

Comparison of Empty-Cell and Full-Cell Treatment of Red Pine and Lodgepole Pine Pole Sections With CCA-PEG, P.A. Cooper, Y.T. Ung, and C. Timusk, 4:13-18 (No. 8082).

Dahurian Larch: Treatment With Inorganic Arsenical Perservatives, J.J. Morrell and P.F. Schneider, 10:61-62 (No. 8162).

Distribution of Biocides in Douglas-fir Poles 42 Months After Application of Groundline Preservative Systems, J.J. Morrell, P.G. Forsyth, and M.A. Newbill, 6:24-27 (No. 8120).

Effects of Long-Term Elevated Temperature on CCA-Treated Southern Pine Lumber, J.E. Winandy, 6:49-56 (No. 8114).

Efficacy of Pressure Treating Northeastern Red Spruce With CCA Using the Pulsation Process, K.A. Flynn and B.S. Goodell, 10:47-49 (No. 8154).

Fire Resistance of Preservative-Treated Slash Pine Fence Posts, P.D. Evans, P. Beutel, R.B. Cunningham, and C.F. Donnelly, 9:37-39 (No. 8135).

Fungal Decay Resistance of Aspen Blocks Treated With Heartwood Extracts, D.P. Kamdem, 1:30-32 (No. 8031).

Increased Wood-Cement Compatibility of Chromate-Treated Wood, R. Schmidt, R. Marsh, J.J. Balatinecz, and P.A. Cooper, 7/8:44-46 (No. 8111).

The Mechanical Properties of Boards Treated With Vapor Boron, R. Hashim, R.J. Murphy, D.J. Dickinson, and J.M. Dinwoodie, 10:73-79 (No. 8160).

Methyl Bromide Fumigation to Control Non-Microbial Discolorations in Western Hemlock and Red Alder, B. Kreber, E.L. Schmidt, and T. Byrne, 10:63-67 (No. 8150).

Natural Resistance of Alaska-cedar, Redwood, and Teak to Formosan Subterranean Termites, J.K. Grace and R.T. Yamamoto, 3:41-45 (No. 8062).

A Preliminary Report on the Wood Preservative Properties of Phenylboronic Acid, X. Liu, P.E. Laks, and M.S. Pruner, 6:46-49 (No. 8128).

Prevention of Enzyme Stain of Hardwoods by Log Fumigation, E.L. Schmidt and T.L. Amburgey, 5:32-34 (No. 8068).

Protection of Western Redcedar Pole Sapwood by Spray Treatments, P. Schneider, J.J. Morrell, and M.A. Newbill, 6:56-61 (No. 8112).

Repeated Exposure of Borate-Treated Douglas-fir Lumber to Formosan Subterranean Termites in an Accelerated Field Test, J.K. Grace and R.T. Yamamoto, 1:65-67 (No. 8007).

Ten-Year Field Performance of CCA-Treated Pine, Cypress, and Eucalypt Poles and Fenceposts in Columbia, J.A. Wright and W.F. Ladrach, 4:69-71 (No. 8058).

Treatability of Lodgepole Pine Laminated Veneer Lumber, P.C. Gomben and T.M. Gorman, 2:39-41 (No. 7967).

Treatability of Western Softwood and Red Alder Shakes, R.C. De Groot, 7/8:34-43 (No. 8115).

Use of Disodium Octaborate Tetrahydrate to Protect Aspen Waferboard From Termites, T.G. Myles, 9:33-36 (No. 8143).

Why Does Douglas-fir Heartwood Turn Black When Treated With Ammoniacal Copper Preservatives? J.N.R. Ruddick and C. Xie, 2:57-61 (No. 8054).

Tropical Woods

Selected Physical and Mechanical Properties of Giant Timber Bamboo Grown in South Carolina, A.W.C. Lee, X. Bai, and P.N. Peralta, 9:40-46 (No. 8145).

WOOD ENGINEERING

Fire Performance & Technology

Fire Resistance of Preservative-Treated Slash Pine Fence Posts, P.D. Evans, P. Beutel, R.B. Cunningham, and C.F. Donnelly, 9:37-39 (No. 8135).

Laminated Wood Components & Engineered Structures

Characteristics of Creosote-Treated LVL Materials, J.D. Kimmel, J.J. Janowiak, R.T. Baileys, and P. Merrick, 5:49-53 (No. 8108).

Compression Strength Properties for Two Hardwood Glulam Materials, J.J. Janowiak, K.R. Kessler, H.B. Manbeck, P.R. Blanken-

horn, and P. Labosky, 2:62-64 (No. 8045).

Effects of Resin Impregnation and Process Parameters on Some Properties of Poplar LVL, Y.H. Chui, M.H. Schneider, and H.J. Zhang, 7/8:74-78 (No. 8070).

Finite Element Analysis of Finger-Joints in Lumber With Dissimilar Laminate Stiffnesses, P.J. Pellicane, 3:17-22 (No. 8072).

Localized Modulus-of-Elasticity Properties of E-Rated Spruce-Pine Laminating Lumber, R. Govindarajoo, R.F. Pellerin, and R.J. Ross, 4:25-32 (No. 8061).

Performance of Oak Strip Flooring Systems Under Changing Environmental Conditions, E.M. Lang, J.R. Loferski, T.E. McLain, and C.M. Moore, 5:54-61 (No. 7993).

Safety Factors for Metal-Plate-Connected Wood Trusses: Theoretical Design Versus Test Specifications, T.D. Skaggs, F.E. Woeste, J.D. Dolan, and J.R. Loferski, 9:11-18 (No. 8131).

Shear Strength of Unchecked Glued-Laminated Beams, L.A. Soltis and D.R. Rammer, 1:51-57 (No. 8010).

Stiffness of Nailed OSB-to-Lumber Connections, M.A.H. Mohammad and I. Smith, 11/12:37-44 (No. 8151).

Treatability of Lodgepole Pine Laminated Veneer Lumber, P.C. Gomben and T.M. Gorman, 2:39-41 (No. 7967).

Mechanical Fastening

Characteristic Strength of Nailed Joints, H.J. Blass, 4:33-39 (No. 8026).

Effect of Moisture Cycling on Truss-Plate Joint Behavior, L.H. Groom, 1:21-29 (No. 7988).

Safety Factors for Metal-Plate-Connected Wood Trusses: Theoretical Design Versus Test Specifications, T.D. Skaggs, F.E. Woeste, J.D. Dolan, and J.R. Loferski, 9:11-18 (No. 8131).

Variation of Load-Slip Behavior in Nailed Joints: Variation Parallel to the Grain, H.J. Blass, 1:15-20 (No. 8027).

Variation of Load-Slip Behavior in Nailed Joints: Variation Perpendicular to the Grain, H.J. Blass, 2:30-34 (No. 8025).

Wood Engineering & Mechanical Properties

Characteristic Strength of Nailed Joints, H.J. Blass, 4:33-39 (No. 8026).

A Comparison of Some Physical and Mechanical Properties of Full-Sib and Half-Sib Loblolly Pines, R.H. McAlister and H.R. Powers, 2:42-44 (No. 7987).

Compression Strength Properties for Two Hardwood Glulam Materials, J.J. Janowiak, K.R. Kessler, H.B. Manbeck, P.R. Blankenhorn, and P. Labosky, 2:62-64 (No. 8045).

Compressive Strength of Hardwood-Cement Composites, P.R. Blankenhorn, P. Labosky, Jr., M. DiCola, and L.R. Stover, 4:59-62 (No. 7962).

Creep Behavior of Sweetgun OSB: Effect of Load Level and Relative Humidity, J.H. Pu, R.C. Tang, and C.Y. Hse, 11/12:45-50 (No. 8064).

Development of the Five-Point Bending Test to Determine Shear Moduli of Wood Composites, J.P. Bradtmueller, M.O. Hunt, K.J. Fridley, and G.P. McCabe, 5:17-26 (No. 8090).

The Durability of Phenolic-Bonded Particleboards Made of Decay-Resistant Black Locust and Nondurable Aspen, D.P. Kamdem and S.T. Sean, 2:65-68 (No. 8016).

Effect of Moisture Cycling on Truss-Plate Joint Behavior, L.H. Groom, 1:21-29 (No. 7988).

Effect of Polyisocyanate Level on Physical Properties of Wood Fiber Composite Materials, B.C.H. Sun, R.N. Hawke, and M.R. Gale, 4:53-58 (No. 7979).

Effect of Polyisocyanate Level on Strength Properties of Wood Fiber Composite Materials, B.C.H. Sun, R.N. Hawke, and M.R. Gale, 3:34-40 (No. 7978).

The Effects of Directed Diffusion on the Mechano-Sorptive Behavior of Small Redwood Beams, W. Lu and R.W. Erickson, 1:8-14 (No. 8015).

Finite Element Analysis of Finger-Joints in Lumber With Dissimilar Laminate Stiffnesses, P.J. Pellicane, 3:17-22 (No. 8072).

Localized Modulus-of-Elasticity Properties of E-Rated Spruce-Pine Laminating Lumber, R. Govindarajoo, R.F. Pellerin, and R.J. Ross, 4:25-32 (No. 8061).

Marketing Practices in the Timber Bridge Industry, R.L. Smith and R.J. Bush, 11/12:27-33 (No. 8163).

Mathematical Details of the Flow-Grain Predictor of Grain Orientation, P.J. Pellicane, 7/8:51-54 (No. 8142).

The Mechanical Properties of Boards Treated With Vapor Boron, R. Hashim, R.J. Murphy, D.J. Dickinson, and J.M. Dinwoodie, 10:73-79 (No. 8160).

A Method of Testing the Full Cross Section of Wood in Tension Perpendicular to the Grain, T.D. Faust, M. Fuller, and J.T. Rice, 3:23-26 (No. 7976).

Selected Physical and Mechanical Properties of Giant Timber Bamboo Grown in South Carolina, A.W.C. Lee, X. Bai, and P.N. Peralta, 9:40-46 (No. 8145).

Shear and Compression Perpendicular to Grain Property Estimation for 2400f MSR Lumber, D.W. Green, D.E. Kretschmann, and J.A. Fantozzi, 11/12:75-81 (No. 8079).

Shear Strength of Unchecked Glued-Laminated Beams, L.A. Soltis and D.R. Rammer, 1:51-57 (No. 8010).

Stiffness of Nailed OSB-to-Lumber Connections, M.A.H. Mohammad and I. Smith, 11/12:37-44 (No. 8151).

Stress Wave Nondestructive Evaluation of Wetwood, R.J. Ross, J.C. Ward, and A. Ten-Wolde, 7/8:79-83 (No. 8136).

Variation in Selected Properties of Industrial Grade Particleboard, D.L. Cassens, J.P. Bradtmueller, and F. Picado, 10:50-56 (No. 8144).

Variation of Load-Slip Behavior in Nailed Joints: Variation Parallel to the Grain, H.J. Blass, 1:15-20 (No. 8027).

Variation of Load-Slip Behavior in Nailed Joints: Variation Perpendicular to the Grain, H.J. Blass, 2:30-34 (No. 8025).

A

Amburgey, T.L., see Schmidt, E.L.

Annavajjhala, R., see Klinkhachorn, R.

Araman, P.A., see Forbes, C.L.

Araman, P.A., see Lin, W.

Armstrong, J.P. and T.L. Pahl, Changes in the Kiln-Drying Practices of the Forest Products Industry in West Virginia: 1982 to 1992, 9:54-56 (No. 8134).

Armstrong, J.P., see Patterson, D.W.

Åstrand, E. and M. Rönnqvist, Crosscut Optimization of Boards Given Complete Defect Information, 2:15-24 (No. 8008).

Avramidis, S., F. Liu, and B.J. Neilson, Radio-Frequency/Vacuum Drying of Softwoods: Drying of Thick Western Redcedar With Constant Electrode Voltage, 1:41-47 (No. 8004).

Avramidis, S., see Dwinell, L.D.

Avramidis, S., see Liu, F.

B

Bai, X., see Lee, A.W.C.

Baileys, R.T., see Kimmel, J.D.

Balatinecz, J.J., see Schmidt, R.

Baldwin, V.C., see Clark, A., III.

Bankston, J.R., see Cassens, D.L.

Bendtsen, B.A., see Ying, L.

Beutel, P., see Evans, P.D.

Blankenhorn, P.R., P. Labosky, Jr., M. DiCola, and L.R. Stover, Compressive Strength of Hardwood-Cement Composites, 4:59-62 (No. 7962).

Blankenhorn, P.R., see Janowiak, J.J.

Blass, H.J., Characteristic Strength of Nailed Joints, 4:33-39 (No. 8026).

Blass, H.J., Variation of Load-Slip Behavior in Nailed Joints: Variation Parallel to the Grain, 1:15-20 (No. 8027).

Blass, H.J., Variation of Load-Slip Behavior in Nailed Joints: Variation Perpendicular to the Grain, 2:30-34 (No. 8025).

Blinn, C.R., see Smidt, M.F.

Boone, R.S., see Rice, R.W.

Bower, D.R., see Clark, A., III.

Bradtmueller, J.P., M.O. Hunt, K.J. Fridley, and G.P. McCabe, Development of the Five-Point Bending Test to Determine Shear Moduli of Wood Composites, 5:17-26 (No. 8090).

Bradtmueller, J.P., see Cassens, D.L.

Bragg, W.C., W.D. Ostrofsky, and B.F. Hoffman, Jr., Residual Tree Damage Estimates From Partial Cutting Simulation, 7/8:19-22 (No. 8077).

Bush, R.J., see Christoforo, J.D.

Bush, R.J., see Forbes, C.L.

Bush, R.J., see Ifju, P.A.

Bush, R.J., see Smith, R.L.

Byrne, A., see Kreber, B.

C

Calloway, J.A., see Suter, W.C., Jr.

Carll, C.G., Basic Mechanical Properties of Flakeboards from Ring-Cut Flakes of Eastern Hardwoods, 9:26-32 (No. 8105).

Carruth, J.S., see Greene, W.D.

Cassens, D.L., J.R. Bankston, and J.S. Friday, Statistical Process Control of Hardwood Lumber Target Sizes: Is It Time? 1:48-50 (No. 7971).

Cassens, D.L., J.P. Bradtmueller, and F. Picado, Variation in Selected Properties of Industrial Grade Particleboard, 10:50-56 (No. 8144).

Cave, I.D. and J.C.F. Walker, Stiffness of Wood in Fast-Grown Plantation Softwoods: The Influence of Microfibril Angle, 5:43-48 (No. 8087).

Chen, Z., E.M. Wengert, and F.M. Lamb, A Technique to Electrically Measure the Moisture Content of Wood Above Fiber Saturation, 9:57-62 (No. 8053).

Christoforo, J.D., R.J. Bush, and W.G. Luppold, A Profile of the U.S. Pallet and Container Industry, 2:9-14 (No. 8047).

Chui, Y.H., M.H. Schneider, and H.J. Zhang, Effects of Resin Impregnation and Process Parameters on Some Properties of Poplar LVL, 7/8:74-78 (No. 8070).

Clark, A., III, J.R. Saucier, V.C. Baldwin, and D.R. Bower, Effect of Initial Spacing and Thinning on Lumber Grade, Yield, and Strength of Loblolly Pine, 11/12: 14-20 (No. 8159).

Clark, J.E., see Dwinell, L.D.

Cohen, D.H., see Maness, T.C.

Cooper, P.A., Y.T. Ung, and C. Timusk, Comparison of Empty-Cell and Full-Cell Treatment of Red Pine and Lodgepole Pine Pole Sections With CCA-PEG, 4:13-18 (No. 8082).

Cooper, P.A., see Schmidt, R.

Corcoran, T.J., see Linehan, P.E.

Cunningham, R.B., see Evans, P.D.

D

Davalos, J.F., see Gardner, D.J.

De Groot, R.C., Treatability of Western Softwood and Red Alder Shakes, 7/8:34-43 (No. 8115).

Dempsey, G.P., see Luppold, W.G.

Dickinson, D.J., see Hashim, R.

DiCola, M., see Blankenhorn, P.R.

Dinwoodie, J.M., see Hashim, R.

Dolan, J.D., see Skaggs, T.D.

Donnelly, C.F., see Evans, P.D.

Duke, C.R., see Horton, C.T.

Duke, C.R., see Syme, J.H.

Dwinell, L.D., S. Avramidis, and J.E. Clark, Evaluation of a Radio-Frequency/Vacuum Dryer for Eradicating the Pinewood Nematode in Green Sawn Wood, 4:19-24 (No. 8050).

E

Eckelman, C.A., see Ho, C.L.

Erickson, R.W., see Lu, W.

Evans, P.D., P. Beutel, R.B. Cunningham, and C.F. Donnelly, Fire Resistance of Preservative -Treated Slash Pine Fence Posts, 9:37-39 (No. 8135).

F

Fahey, T.D., see Lowell, E.C.

Fantozzi, J.A., see Green, D.W.

Faust, T.D., M. Fuller, and J.T. Rice, A Method of Testing the Full Cross Section of Wood in Tension Perpendicular to the Grain, 3:23-26 (No. 7976).

Feist, W.C., Weathering Performance of Finished Aspen Siding, 6:15-24 (No. 8122).

Feist, W.C., see Kropf, F.W.

Flynn, K.A. and B.S. Goodell, Efficacy of Pressure Treating Northeastern Red Spruce With CCA Using the Pulsation Process, 10:47-49 (No. 8154).

Forbes, C.L., S.A. Sinclair, R.J. Bush, and P.A. Araman, Influence of Product and Supplier Attributes on Hardwood Lumber Purchase Decisions in the Furniture Industry, 2:51-56 (No. 8048).

Forsyth, P.G., see Morrell, J.J.

Friday, J.S., see Cassens, D.L.

Fridley, K.J., see Bradtmueller, J.P.

Fuller, M., see Faust, T.D.

G

Gale, M.R., see Sun, B.C.H.

Gardner, D.J., J.F. Davalos, and U.M. Munipalle, Adhesive Bonding of Pultruded Fiber Reinforced Plastic to Wood, 5:62-66 (No. 8104).

Geimer, R.L., see Jokerst, R.W.

Glossop, B.R., Effect of Hot-Water Soaking or Freezing Pre-treatments on the Drying Rates of Two Eucalypts, 10:29-32 (No. 7959).

Gomben, P.C. and T.M. Gorman, Treatability of Lodgepole Pine Laminated Veneer Lumber, 2:39-41 (No. 7967).

Goodell, B.S., see Flynn, K.A.

Gorman, T.M., see Gomben, P.C.

Govindarajoo, R., R.F. Pellerin, and R.J. Ross, Localized Modulus-of-Elasticity Properties of E-Rated Spruce-Pine Laminating Lumber, 4:25-32 (No. 8061).

Grace, J.K. and R.T. Yamamoto, Natural Resistance of Alaska-cedar, Redwood, and Teak to Formosan Subterranean Termites, 3:41-45 (No. 8062).

Grace, J.K. and R.T. Yamamoto, Repeated Exposure of Borate-Treated Douglas-fir Lumber to Formosan Subterranean Termites in an Accelerated Field Test, 1:65-67 (No. 8007).

Green, D.W., D.E. Kretschmann, and J.A. Fantozzi, Shear and Compression Perpendicular to Grain Property Estimation for 2400f MSR Lumber, 11/12:75-81 (No. 8079).

Greene, W.D. and J.S. Carruth, Log Separation Economics on In-Woods Chipping Operations, 10:68-72 (No. 8152).

Groom, L.H., Effect of Moisture Cycling on Truss-Plate Joint Behavior, 1:21-29 (No. 7988).

Groom, L., see Liang, B-H.

Gutkowski, R.M., see Pellicane, P.J.

H

Harless, T.E.G., see Steele, P.H.

Hashim, R., R.J. Murphy, D.J. Dickinson, and J.M. Dinwoodie, The Mechanical Properties of Boards Treated With Vapor Boron, 10:73-79 (No. 8160).

Haupt, R.A. and T. Sellers, Jr., Phenolic Resin-Wood Interaction, 2:69-73 (No. 8030).

Haupt, R.A., see Sellers, T., Jr.

Hawke, R.N., see Sun, B.C.H.

Heissenbuttel, J., see Schallau, C.

Hernández, R.E., Effect of Two Wood Surfacing Methods on the Gluing Properties of Sugar Maple and White Spruce, 7/8:63-66 (No. 8088).

Ho, C.L. and C.A. Eckelman, The Use of Performance Tests in Evaluating Joint and Fastener Strength in Case Furniture, 9:47-53 (No. 7922).

Hoffman, B.F., Jr., see Bragg, W.C.

Horton, C.T., J.H. Syme, C.R. Duke, and T.J. Straka, Distribution and Marketing of Southern Yellow Pine Shakes: Potential for Expansion, 11/12:21-26 (No. 8156).

Howe, J.L., see Rice, R.W.

Hse, C.Y., see Pu, J.H.

Hunt, M.O., see Bradtmueller, J.P.

I

Idassi, J.O., T.M. Young, P.M. Winistorfer, D.M. Ostermeier, and R.B. Woodruff, Customer-Oriented Marketing Method for Hardwood Lumber Companies, 7/8:67-73 (No. 8003).

Ifju, P.A. and R.J. Bush, Export Assistance in the Hardwood Industry: An Examination of Awareness, Use, and Perceived Benefit, 6:27-33 (No. 8071).

Isaacson, R.L., see Tiedeman, G.T.

J

Janowiak, J.J., K.R. Kessler, H.B. Manbeck, P.R. Blankenhorn, and P. Labosky, Compression Strength Properties for Two Hardwood Glulam Materials, 2:62-64 (No. 8045).

Janowiak, J.J., see Kimmel, J.D.

Jauslin, C., see Pellicane, P.J.

Johnson, B.N., Inventory of Land Management Inputs for Producing Absorbent Fibers for Diapers: A Comparison of Cotton and Softwood Land Management, 6:39-46 (No. 8103).

Johnson, S.E. and F.A. Kamke, Carbohydrate-Based Extender for Wood-Particulate Composites, 3:46-48 (No. 7879)

Jokerst, R.W. and R.L. Geimer, Steam-Assisted Hot-Pressing of Construction Plywood, 11/12:34-36 (No. 7838).

K

Kamdem, D.P., Fungal Decay Resistance of Aspen Blocks Treated With Heartwood Extracts, 1:30-32 (No. 8031).

Kamdem, D.P. and S.T. Sean, The Durability of Phenolic-Bonded Particleboards Made of Decay-Resistant Black Locust and Nondurable Aspen, 2:65-68 (No. 8016).

Kamke, F.A., see Johnson, S.E.

Kessler, K.R., see Janowiak, J.J.

Kim, M.G., see Oh, Y.

Kim, M.G., see Sellers, T., Jr.

Kimmel, J.D., J.J. Janowiak, R.T. Baileys, and P. Merrick, Characteristics of Creosote-Treated LVL Materials, 5:49-53 (No. 9108).

Kline, D.E., see Lin, W.

Klinkhachorn, R., R. Kothari, R. Annavajjhala, and C.W. McMillin, TRSys: A Hardwood Lumber Grading Training and Remanufacturing System, 9:68-72 (No. 7916).

Kothari, R., see Klinkhachorn, R.

Kreber, B. and A. Byrne, Discolorations of Hem-fir Wood: A Review of the Mechanisms, 5:35-42 (No. 8093).

Kreber, B., E.L. Schmidt, and T. Byrne, Methyl Bromide Fumigation to Control Non-Microbial Discolorations in Western Hemlock and Red Alder, 10:63-67 (No. 8150).

Kretschmann, D.E., see Green, D.W.

Kretschmann, D.E., see Ying, L.

Kropf, F.W., J. Sell, and W.C. Feist, Comparative Weathering Tests of North American and European Exterior Wood Finishes, 10:33-41 (No. 8132).

Kumar, L., see Steele, P.H.

L

Labosky, P., Jr., see Blankenhorn, P.R.

Labosky, P., see Janowiak, J.J.

Ladrach, W.F., see Wright, J.A.

Laks, P.E., see Liu, X.

Lamb, F.M., see Chen, Z.

Lang, E.M., J.R. Loferski, T.E. McLain, and C.M. Moore, Performance of Oak Strip Flooring Systems Under Changing Environmental Conditions, 5:54-61 (No. 7993).

Lee, A.W.C., X. Bai, and P.N. Peralta, Selected Physical and Mechanical Properties of Giant Timber Bamboo Grown in South Carolina, 9:40-46 (No. 8145).

Lee, S., see Steele, P.H.

Liang, B-H., S.M. Shaler, L. Mott, and L. Groom, Recycled Fiber Quality From a Laboratory-Scale Blade Separator/Blender, 7/8:47-50 (No. 8113).

Lin, W., D.E. Kline, and P.A. Araman, Dimension Yields From Factory Grade 2 and 3 Red Oak Logs, 9:19-25 (No. 8109).

Linehan, P.E. and T.J. Corcoran, An Expert System for Timber Harvesting Decision Making on Industrial Forest Lands, 6:65-71 (No. 8092).

Liu, F., S. Avramidis, and R.L. Zwick, Drying Thick Western Hemlock in a Laboratory Radio-Frequency/Vacuum Dryer With Constant and Variable Electrode Voltage, 6:71-76 (No. 8099).

Liu, F., see Avramidis, S.

Liu, X., P.E. Laks, and M.S. Pruner, A Preliminary Report on the Wood Preservative Properties of Phenylboronic Acid, 6:46-49 (No. 8128).

Loehnertz, S.P., see Simpson, W.T.

Loferski, J.R., see Lang, E.M.

Loferski, J.R., see Skaggs, T.D.

Lowell, E.C. and T.D. Fahey, The Effect of Frost Cracks in Sugar Pine Trees on Lumber Grade, 10:57-60 (No. 8033).

Lu, W. and R.W. Erickson, The Effects of Directed Diffusion on the Mechano-Sorptive Behavior of Small Redwood Beams, 1:8-14 (No. 8015).

Luppold, W.G., The U.S. Hardwood Log Export Situation: What is the Problem? 9:63-67 (No. 8155).

Luppold, W.G. and G.P. Dempsey, Factors Affecting Regional Changes in Hardwood Lumber Production, 6:8-15 (No. 7974).

Luppold, W.G., see Christoforo, J.D.

M

Manbeck, H.B., see Janowiak, J.J.

Maness, T.C., Benefits From Market Timing Controls in Sawmill Production Management, 5:27-31 (No. 8091).

Maness, T.C., D.H. Cohen, and R. Smith, An Assessment of Quality Control in British Columbia Sawmills: Production, Employment, Trends, and Priorities, 3:27-33 (No. 8001).

Marsh, R., see Schmidt, R.

McAlister, R.H. and H.R. Powers, A Comparison of Some Physical and Mechanical Properties of Full-Sib and Half-Sib Loblolly Pines, 2:42-44 (No. 7987).

McCabe, G.P., see Bradtmueller, J.P.

McKeever, D.B. and R.B. Phelps, Wood Products Used in New Single-Family House Construction: 1950 to 1992, 11/12:66-74 (No. 8169).

McLain, T.E., see Lang, E.M.

McMillin, C.W., see Klinkhachorn, R.

McNeel, J.F. and G.G. Young, Optimal Yarding Road Width Model for Skyline Yarding, 2:45-50 (No. 7992).

Meilke, K.D., see Puttock, G.D.

Merrick, P., see Kimmel, J.D.

Michael, J.H. and P.M. Smith, Furniture Markets as Promotional Tools: Integrating Objectives for Furniture Manufacturers, 11/12: 51-54 (No. 8138).

Miller, G.D., see Sellers, T., Jr.

Milota, M.R., Specific Gravity as a Predictor of Species Correction Factors for a Capacitance-Type Moisture Meter, 3:63-68 (No. 8066).

Mohammad, M.A.H. and I. Smith, Stiffness of Nailed OSB-to-Lumber Connections, 11/12: 37-44 (No. 8151).

Moore, C.M., See Lang, E.M.

Morrell, J.J. and P.F. Schneider, Dahurian Larch: Treatment With Inorganic Arsenical Perservatives, 10:61-62 (No. 8162).

Morrell, J.J., P.G. Forsyth, and M.A. Newbill, Distribution of Biocides in Douglas-fir Poles 42 Months After Application of Groundline Preservative Systems, 6:24-27 (No. 8120).

Morrell, J.J., see Schneider, P.

Mothe, F., see Zhang, S.Y.

Mott, L., see Liang, B-H.

Munipalle, U.M., see Gardner, D.J.

Munk, W.P. and B. Shane, Using Competitive Analysis Models to Set Strategy in the Northwest Hardboard Industry, 7/8:11-18 (No. 7995).

Murphy, R.J., see Hashim, R.

Myles, T.G., Use of Disodium Octaborate Tetrahydrate to Protect Aspen Waferboard From Termites, 9:33-36 (No. 8143).

N

Neilson, B.J., see Avramidis, S.

Nepveu, G., see Zhang, S.Y.

Newbill, M.A., see Morrell, J.J.

Newbill, M.A., see Schneider, P.

O

Oh, Y., T. Sellers, Jr., M.G. Kim, and R.C. Strickland, Evaluation of Phenol-Formaldehyde OSB Resins Modified With Lignin Residues From Acid-Hydrolyzed Waste Newsprint, 2:25-29 (No. 8042).

Ostermeier, D.M., see Idassi, J.O.

Ostrofsky, W.D., see Bragg, W.C.

P

Pahl, T.L., see Armstrong, J.P.

Park, J.C., Evaluating Pruned Sawlog Quality and Assessing Sawmill Recoveries in New Zealand, 4:43-52 (No. 8044).

Patterson, D.W. and J.P. Armstrong, Prediction Equations for Determining Board Foot Recovery From Bolter Saw Bolts, 4:40-42 (No. 8084).

Pellerin, R.F., see Govindarajoo, R.

Pellicane, P.J., Finite Element Analysis of Finger-Joints in Lumber With Dissimilar Laminate Stiffness, 3:17-22 (No. 8072).

Pellicane, P.J., Mathematical Details of the Flow-Grain Predictor of Grain Orientation, 7/8:51-54 (No. 8142).

Pellicane, P.J., R.M. Gutkowski, and C. Jauslin, Effect of Glueline Voids on the Tensile Strength of Finger-Jointed Wood, 6:61-65 (No. 8129).

Peralta, P.N., see Lee, A.W.C.

Phelps, J.E., D.D. Stokke, and A.D. Pugel, Color Analysis of White Oak, Edge-Glued Furniture Panel Stock, 2:35-38 (No. 8056).

Phelps, R.B., see McKeever, D.B.

Picado, F., see Cassens, D.L.

Powers, H.R., see McAlister, R.H.

Pruner, M.S., see Liu, X.

Pu, J.H., R.C. Tang, and C.Y. Hse, Creep Behavior of Sweetgum OSB: Effect of Load Level and Relative Humidity, 11/12:45-50 (No. 8064).

Pugel, A.D., see Phelps, J.E.

Puttock, G.D., M. Sabourin, and K.D. Meilke, International Trade in Forest Products: An Overview, 3:49-56 (No. 8067).

R

Rammer, D.R., see Soltis, L.A.

Reisinger, T.W., R.G. Sluss, and R.M. Shaffer, Managerial and Operational Characteristics of "Safety Successful" Logging Contractors, 4:72-77 (No. 8065).

Rice, J.T., see Faust, T.D.

Rice, R.W., J.L. Howe, R.S. Boone, and J.L. Tschernitz, A Survey of Firms Kiln-Drying Lumber in the United States: Volume, Species, Kiln Capacity, Equipment, and Procedures, 7/8:55-62 (No. 8149).

River, B.H., Outdoor Aging of Wood-Based Panels and Correlation With Laboratory Aging, 11/12:55-65 (No. 8106).

Ronnqvist, M., see Astrand, E.

Ross, R.J., J.C. Ward, and A. TenWolde, Stress Wave Nondestructive Evaluation of Wetwood, 7/8:79-83 (No. 8136).

Ross, R.J., see Govindarajoo, R.

Ruddick, J.N.R. and C. Xie, Why Does Douglas-fir Heartwood Turn Black When Treated With Ammoniacal Copper Preservatives? 2:57-61 (No. 8054).

S

Sabourin, M., see Puttock, G.D.

Saucier, J.R., see Clark, A., III.

Schallau, C., J. Heissenbuttel, and R. Pierson, Regulating for Sustained Yield: A Review of Some Fundamental Relationships, 7/8:23-26 (No. 8100).

Schmidt, E.L. and T.L. Amburgey, Prevention of Enzyme Stain of Hardwoods by Log Fumigation, 5:32-34 (No. 8068).

Schmidt, E.L., see Kreber, B.

Schmidt, R., R. Marsh, J.J. Balatinecz, and P.A. Cooper, Increased Wood-Cement Compatibility of Chromate-Treated Wood, 7/8:44-46 (No. 8111).

Schneider, M.H., see Chui, Y.H.

Schneider, P., J.J. Morrell, and M.A. Newbill, Protection of Western Redcedar Pole Sapwood by Spray Treatments, 6:56-61 (No. 8112).

Schneider, P.F., see Morrell, J.J.

Sean, S.T., see Kamdem, D.P.

Sell, J., see Kropf, F.W.

Sellers, T., Jr., Information Processing Systems for General Access of Unpublished Wood Products Research Data, 6:33-39 (No. 8041).

Sellers, T., Jr., M.G. Kim, G.D. Miller, R.A. Haupt, and R.C. Strickland, Comparison of Strandboards Made With Phenol-Formaldehyde Resin and Resins Modified With TVA Acid-Hydrolysis Lignin, 4:63-68 (No. 8022).

Sellers, T., Jr., see Haupt, R.A.

Sellers, T., Jr., see Oh, Y.

Sellers, T., Jr., see Tiedeman, G.T.

Shaffer, R.M., see Reisinger, T.W.

Shane, B., see Munk, W.P.

Shaler, S.M., see Liang, B-H.

Simpson, W.T. and S.P. Loehnertz, Resistance Moisture Meter Correction Factor for Pacific Yew, 1:63-64 (No. 8020).

Sinclair, S.A., see Forbes, C.L.

Skaggs, T.D., F.E. Woeste, J.D. Dolan, and J.R. Loferski, Safety Factors for Metal-Plate-Connected Wood Trusses: Theoretical Design Versus Test Specifications, 9:11-18 (No. 8131).

Sluss, R.G. see Reisinger, T.W.

Smidt, M.F. and C.R. Blinn, Evaluation of Logger Continuing Education Needs in Minnesota, 3:57-62 (No. 8034).

Smith, I., see Mohammad, M.A.H.

Smith, P.M., see Michael, J.H.

Smith, P.M., see Vlosky, R.P.

Smith, R., see Maness, T. C.

Smith, R.L. and R.J. Bush, Marketing Practices in the Timber Bridge Industry, 11/12:27-33 (No. 8163).

Soltis, L.A. and D.R. Rammer, Shear Strength of Unchecked Glued-Laminated Beams, 1:51-57 (No. 8010).

Steele, P.H. and S. Lee, Yield Comparisons of Furniture Parts for Three Gang-Ripping Systems, 3:9-16 (No. 8009).

Steele, P.H., T.E.G. Harless, F.G. Wagner, L. Kumar, and F.W. Taylor, Increased Lumber Value From Optimum Orientation of Internal Defects With Respect to Sawing Pattern in Hardwood Sawlogs, 3:69-72 (No. 7871).

Stokke, D.D., see Phelps, J.E.

Stover, L.R., see Blankenhorn, P.R.

Straka, T.J., see Horton, C.T.

Strickland, R.C., see Oh, Y.

Strickland, R.C., see Sellers, T., Jr.

Sun, B.C.H., R.N. Hawke, and M.R. Gale, Effect of Polyisocyanate Level on Physical Properties of Wood Fiber Composite Materials, 4:53-58 (No. 7979).

Sun, B.C.H., R.N. Hawke, and M.R. Gale, Effect of Polyisocyanate Level on Strength Properties of Wood Fiber Composite Materials, 3:34-40 (No. 7978).

Suter, W.C., Jr. and J.A. Calloway, Rough Mill Policies Examined by a Multiple-Criteria Goal Program Called ROMGOP, 10:19-28 (No. 8069).

Syme, J.H. and C.R. Duke, Market-Oriented Strategy for Forest-Based Rural Economic Development, 5:10-16 (No. 8028).

Syme, J.H., see Horton, C.T.

T

Tang, R.C., see Pu, J.H.

Taylor, F.W., see Steele, P.H.

TenWolde, A., see Ross, R.J.

Tiedeman, G.T., R.L. Isaacson, and T. Sellers, Jr., Total Phenolic Compounds and Free Phenol in Softwood Structural Plywood, 3:73-75 (No. 8043).

Timusk, C., see Cooper, P.A.

Tschernitz, J.L., see Rice, R.W.

U

Ung, Y.T., see Cooper, P.A.

V

Vick, C.B., Phenolic Adhesive Bonds to Aspen Veneers Treated With Amino-Resin Fire Retardants, 1:33-40 (No. 7977).

Vlosky, R.P. and P.M. Smith, The Retail Homecenter Perspective on Point-of-Sale Scanning of UPC Barcoded Wood Products, 7/8:27-33 (No. 8107).

W

Wagner, F.G., see Steele, P.H.

Walker, J.C.F., see Cave, I.D.

Ward, J.C., see Ross, R.J.

Warsco, K., Conventional Fuel Displacement by Residential Wood Use, 1:68-74 (No. 7900).

Wengert, E.M., see Chen, Z.

Winandy, J.E., Effects of Long-Term Elevated Temperature on CCA-Treated Southern Pine Lumber, 6:49-56 (No. 8114).

Winistorfer, P.M., see Idassi, J.O.

Woeste, F.E., see Skaggs, T.D.

Woodruff, R.B., see Idassi, J.O.

Wright, J.A. and W.F. Ladrach, Ten-Year Field Performance of CCA-Treated Pine, Cypress, and Eucalypt Poles and Fenceposts in Columbia, 4:69-71 (No. 8058).

X

Xie, C., see Ruddick, J.N.R.

Y

Yamamoto, R.T., see Grace, J.K.

Ying, L., D.E. Kretschmann, and B.A. Bendtsen, Longitudinal Shrinkage in Fast-Grown Loblolly Pine Plantation Wood, 1:58-62 (No. 8006).

Young, G.G., see McNeel, J.F.

Young, T.M., see Idassi, J.O.

Z

Zhang, H.J., see Chui, Y.H.

Zhang, S.Y., G. Nepveu, and F. Mothe, Modeling Intratree Wood Shrinkage in European Oak by Measuring Wood Density, 10:42-46 (No. 8086).

Zwick, R.L., see Liu, F.